

4000 dm³ combined vibration and temperature and temperature



4000 dm³ environmental chamber for vibration and temperature combined tests.

Very special machine because of its multivalence, it has been manufactured upon specifications to carry out different standards, mixing wide variation rates, rapid saturation tests and negative dew-points, all of it with a load of about 200 kg.

Very powerful and efficient chamber composed of several independent refrigerating circuits that enable an accurate management of needs. Both airflows are directly blown upon the product to improve the thermal impact.

Numerous technologies are embedded : air dryer, product probe, capacitive measurement, spraying, boiler, phase absence detector, LN2, negative dew-point management.



Dimensions (mm)	W	D	H
Useful	3300	1200	1000

CLIMATS

SPECIAL



Technical features

Temperature range

from +180°C to -70°C

Speed variation

15°C/min average from +70°C to -55°C and the other way round with a 250 kg load

30°C/min average with LN2 as complement from +70°C to -55°C and the other way round with a 250 kg load

Hygrometry

from 20% to 95% humidity in 10 min at +60°C

from 95% to 10% humidity in 10 min at +60°C

Homogeneity and Regulation

Temperature homogeneities (carried out with PT100 probes set at 20 cm from the walls)
below $\pm 2^\circ\text{C}$ up to +100°C

Temperature regulation

$\pm 0,5^\circ\text{C}$ after stabilization

